

PUSHING FOR BETTER SOLUTIONS

PassAbility™



Universal Standard Weatherproof Electromagnetic Lock



FEATURES:

SPECIFICATIONS:

Operating Voltage:

Single Voltage: 12 or 24VDC
Dual Voltage: 12/24VDC

Current Draw:

Single Voltage: 500mA/12VDC, 250mA/24VDC
Dual Voltage: 500mA/12VDC, 250mA/24VDC
(at temperature 20°C)

Operating Temperature: -10~55°C (14~131°F)

Humidity: 0~95% non-condensing.

Holding Force: 1200 lbs (545 Kg)

Bond sensor output: 0.5A/20VDC

Dimensions:

Magnet: (L) 220, (W) 62, (D) 40 mm
Armature Plate: (L) 185, (W) 62, (D) 16 mm

Net Weight: 5.1Kg

Surface finish for magnet and armature plate: Zinc plated

Epoxy potting compound rating: E87252 (S) UL94V-0

FUNCTIONS & FEATURES:

- Low maintenance and high reliability
- Stainless steel casing
- MOV provides spike and surge protection
- Anti-Residual magnetism function
- Holding force up to 1200lbs
- Strengthened mounting plate
- Non-handed install
- IPX7 waterproof rating

7380 S. Eastern Avenue, Suite 124-320 • Las Vegas, NV 89123

All items are trademarks of their respective holders.

To have your fax number removed from future specials, please call Removal Services - 800-915-2571 ext. 47540 or fax to 866-975-0404.