



FEATURES

- Remotely PIN access code changing
- Up to 1000 PIN access codes (4 digits)
- Up to 100 authorized users
- Set up all codes and other parameters via PC or remotely by SMS

APPLICATIONS:

- Restricted access areas
- Barriers
- Entry and garage doors
- Rental apartments



SPECIFICATIONS

Power supply	14.4/24 VDC 12-16 VAC
Current Consumption	
Transmitting Mode	315mA
Idle Mode	272mA
QUAD Band GSM Module	850/900/1800/1900 MHz
Unit Dimensions	6-1/8 x 4-1/2 x 2-3/8 "
External Patch Antenna SMA	1
Front Plate	Grade 304 Stainless Steel

Optional Feature:


Solar Friendly Consumption	
Transmitting Mode	80mA
Idle Mode	32mA

ACCESSORIES

EISWARE

Programming Software

Available on IOS or Android App and online at www.eisware.com.



Search:
EISWARE WEB



Optional receiver and transmitter module for wireless application



2480 South 3850 West, Suite B
Salt Lake City, UT 84120
(866) 975-0101 • (866) 975-0404 fax
www.transmittersolutions.com

All items are trademarks of their respective holders.

To have your fax number removed from future specials, please call Removal Services - 800-915-2571 ext. 47540 or fax to 866-975-0404.