iLA Wi-Plus

Wireless Access Control System





FEATURES

- Uses Wi-Plus range of Door Controls
- Supports Wireless or RS485 Networks
- 60 Doors per System
- 15 Doors per Controller
- 5000 Users (Card/Fob, PIN, Fingerprint)
- · Can Use ACT, HID & Paxton Cards/Fobs
- 16 User Groups, 16 Time Zones
- TCP/IP Network, RS232 & Serial RS485
- Database encryption for maximum security



ADDITIONAL FEATURES

- Reporting Facility in .pdf and .csv formats for:
 - Time & Attendance Event History
 - User Activity
- · Challenge facility
- Unlimited Log
- · On Board Tamper protection
- Tamper Input extendable to Intruder Panel
- Easy Programming via ILA Software
- · Standard, Toggle & Manager Users
- Intruder & Fire Alarm Interface
- Interlock
- 2 On Board 5amp Relays 240vac
- 4 Programmable Inputs & Outputs
- Key Programmable Features:
 - Door Timers Timed ActionsDoor Options Alarm Options
 - User Groups Door Groups
 - Time Zones Number of PIN code Digits
 - Programming Code

- · Robust Polycarbonate Housing
- 2 Year Warranty.
- Upgradable to GSD Wi-Enterprise Access Control using the same Wi-Plus family of door controls.

SPECIFICATIONS		
Power Supply		12 DC
Current consumption		120mA
Current consumption with load (max)		160mA
Moisture Resistance		Indoor Use Only
Dimensions	W. 135mm D. 46mm H. 200mm	



2480 South 3850 West, Suite B Salt Lake City, UT 84120 (866) 975-0101 • (866) 975-0404 fax www.transmittersolutions.com