

PAL

VPS - VIDEO PANEL SYSTEM



Up to 6000 users



Touch Screen
Panel Interface



Cellular Connectivity



Ethernet Connectivity



Cloud based - easy
to use software



Anti Vandal Design



Anti Vandal Glass



Ambient Light
Sensor



Wiegand-26

Features

- VPS is a video telephone entry system, showing a live video feed during calls
- Group Calling
- Built-in multi-protocol reader
- Available Wiegand input for aux. devices, i.e. cards, transmitters, UHF reader, etc.
- Simple, intuitive user portal
- Very low annual renewal cost regardless of # of users
- Custom powder-coated mounting options - hood, post mount adapter, and cabinet pedestal available

Mounting Options

Wall Mount



Post Mount



CLOUD-BASED SOFTWARE

The PAL VPS is operated through an intuitive cloud-based software that gives flexibility to use it from a desktop or through the dedicated PAL application.

You are able to manage multiple access points with a PAL device from a single dashboard, view unlimited event logs, and manage user access. This unparalleled management made easy gives you more power to manage access control.

Specifications

Display Size	7-inch
Display Resolution	720x1280
Camera	8M pixels - View Angle 120°
Cellular network supported	4G / 3G / 2G
Bluetooth	BT4.2 LE
NFC	13.56 MHz
Ethernet	RJ45, 10/100Mbps
Relay	2 * Relays (N.O/N.C)
Input	2 * Input
Supports App	Android / iOS
PoE	Fully-Integrated IEEE 802.3-Compliant POE+ PD Interface
Card reader	NFCIP-1, NFCIP-2, ISO/IEC 14443, ISO/IEC 15693, MIFARE
Audio Interfaces	Speaker: Hidden powerful 15W/4Ω Microphone: -42dB ±3dB @ 94dB SPL
Installation	Wall-mounted Flush-mounthed
Power Supply	DC 48V or/and PoE+
Power Output	DC 12V 2.5A
Working Temperature	-20 to 65°C
Physical Characteristics Size	Size: 251.6 x 129.6 mm
Languages	English,Hebrew,Russian,Spanish,Dutch